

Miscellaneous Shapes

Single Angles

CAFECO® SprayFilm® WB 3 and WB 4 & ISOLATEK® Type WB 3 and WB 4

ASTM Desig.	W/D	Metric Desig.	M/D	Hp/A	1-Hour	1-1/2 Hour	2-Hour	3-Hour
L 8 x 8 x 1-1/8	1.80	203 x 203 x 29	106.2	74.4	0.028	0.056	0.085	0.187
x 1	1.62	x 25	95.6	82.7	0.032	0.061	0.097	0.200
x 7/8	1.43	x 22	84.4	93.7	0.036	0.069	0.109	0.227
x 3/4	1.24	x 19	73.2	108.1	0.040	0.078	0.123	0.255
x 5/8	1.04	x 16	61.4	128.8	0.048	0.095	0.149	0.308
x 9/16	0.94	x 14	55.5	142.5	0.054	0.106	0.167	0.346
x 1/2	0.84	x 13	49.6	159.5	0.057	0.113	0.177	0.367
L8 x 6 x 1	1.60	203 x 152 x 25	94.4	83.7	0.032	0.061	0.097	0.200
x 7/8	1.41	x 22	83.2	95.0	0.036	0.069	0.109	0.227
x 3/4	1.22	x 19	72.0	109.8	0.040	0.078	0.123	0.255
x 5/8	1.03	x 16	60.8	130.1	0.048	0.095	0.149	0.308
x 9/16	0.93	x 14	54.9	144.1	0.054	0.106	0.167	0.346
x 1/2	0.83	x 13	49.0	161.4	0.061	0.121	0.191	0.395
x 7/16	0.73	x 11	43.1	183.5	0.071	0.130	0.213	0.453
L8 x 4 x 1	1.58	203 x 102 x 25	93.2	84.8	0.032	0.061	0.097	0.200
x 7/8	1.40	x 22	82.6	95.7	0.036	0.069	0.109	0.227
x 3/4	1.21	x 19	71.4	110.7	0.040	0.078	0.123	0.255
x 5/8	1.03	x 16	60.8	130.1	0.048	0.095	0.149	0.308
x 9/16	0.92	x 14	54.3	145.6	0.054	0.106	0.167	0.346
x 1/2	0.82	x 13	48.4	163.4	0.061	0.121	0.191	0.395
x 7/16	0.73	x 11	43.1	183.5	0.071	0.130	0.213	0.453
L7 x 4 x 3/4	1.20	178 x x102 x 19	70.8	111.7	0.042	0.083	0.131	0.270
x 5/8	1.01	x 16	59.6	132.7	0.048	0.095	0.149	0.308
x 1/2	0.82	x 13	48.4	163.4	0.061	0.121	0.191	0.395
x 7/16	0.72	x 11	42.5	186.1	0.071	0.130	0.213	0.453
x 3/8	0.62	x 9.5	36.6	216.1	0.075	0.130	0.213	0.504
L6 x 6 x 1	1.58	152 x 152 x 25	93.2	84.8	0.032	0.061	0.097	0.200
x 7/8	1.39	x 22	82.0	96.4	0.036	0.069	0.109	0.227
x 3/4	1.21	x 19	71.4	110.7	0.040	0.078	0.123	0.255
x 5/8	1.02	x 16	60.2	131.4	0.048	0.095	0.149	0.308
x 9/16	0.92	x 14	54.3	145.6	0.054	0.106	0.167	0.346
x 1/2	0.82	x 13	48.4	163.4	0.061	0.121	0.191	0.395
x 7/16	0.72	x 11	42.5	186.1	0.071	0.130	0.213	0.453
x 3/8	0.62	x 9.5	36.6	216.1	0.075	0.130	0.213	0.504
x 5/16	0.52	x 7.9	30.7	257.7	0.092	0.182	0.286	NR
L6 x 4 x 7/8	1.37	152 x 102 x 22	80.8	97.8	0.036	0.069	0.109	0.227
x 3/4	1.19	x 19	70.2	112.6	0.042	0.083	0.131	0.270
x 5/8	1.00	x 16	59.0	134.0	0.048	0.095	0.149	0.308
x 9/16	0.90	x 14	53.1	148.9	0.054	0.106	0.167	0.346
x 1/2	0.80	x 13	47.2	167.5	0.061	0.121	0.191	0.395
x 7/16	0.71	x 11	41.9	188.7	0.071	0.130	0.213	0.453
x 3/8	0.61	x 9.5	36.0	219.6	0.075	0.130	0.213	0.504
x 5/16	0.51	x 7.9	30.1	262.7	0.100	0.197	0.310	NR
L6 x 3.5 x 1/2	0.81	152 x 89 x 13	47.8	165.4	0.061	0.121	0.191	0.395
x 3/8	0.61	x 9.5	36.0	219.6	0.075	0.130	0.213	0.504
x 5/16	0.51	x 7.9	30.1	262.7	0.100	0.197	0.310	NR

Note: All thicknesses are expressed in inches. To convert to Mils, multiply by 1000. To convert to mm, multiply by 25.4

Miscellaneous Shapes

Single Angles

CAFECO® SprayFilm® WB 3 and WB 4 & ISOLATEK® Type WB 3 and WB 4

ASTM Desig.	W/D	Metric Desig.	M/D	Hp/A	1-Hour	1-1/2 Hour	2-Hour	3-Hour
L5 x 5 x 7/8	1.38	127 x 127 x 22	81.4	97.1	0.036	0.069	0.109	0.227
x 3/4	1.20	x 19	70.8	111.7	0.042	0.083	0.131	0.270
x 5/8	1.02	x 16	60.2	131.4	0.048	0.095	0.149	0.308
x 1/2	0.82	x 13	48.4	163.4	0.061	0.121	0.191	0.395
x 7/16	0.72	x 11	42.5	186.1	0.071	0.130	0.213	0.453
x 3/8	0.62	x 9.5	36.6	216.1	0.075	0.130	0.213	0.504
x 5/16	0.52	x 7.9	30.7	257.7	0.092	0.182	0.286	NR
L5 x 3.5 x 3/4	1.18	127 x 89 x 19	69.6	113.5	0.042	0.083	0.131	0.270
x 5/8	1.00	x 16	59.0	134.0	0.048	0.095	0.149	0.308
x 1/2	0.81	x 13	47.8	165.4	0.061	0.121	0.191	0.395
x 3/8	0.61	x 9.5	36.0	219.6	0.075	0.130	0.213	0.504
x 5/16	0.51	x 7.9	30.1	262.7	0.100	0.197	0.310	NR
x 1/4	0.41	x 6.4	24.2	326.8	0.117	0.230	NR	NR
L5 x 3 x 1/2	0.81	127 x 76 x 13	47.8	165.4	0.061	0.121	0.191	0.395
x 7/16	0.71	x 11	41.9	188.7	0.071	0.130	0.213	0.453
x 3/8	0.61	x 9.5	36.0	219.6	0.075	0.130	0.213	0.504
x 5/16	0.51	x 7.9	30.1	262.7	0.100	0.197	0.310	NR
x 1/4	0.41	x 6.4	24.2	326.8	0.117	0.230	NR	NR
L4 x 4 x 3/4	1.17	102 x 102 x 19	69.0	114.5	0.042	0.083	0.131	0.270
x 5/8	0.99	x 16	58.6	134.8	0.050	0.099	0.157	0.324
x 1/2	0.80	x 13	47.2	167.5	0.061	0.121	0.191	0.395
x 7/16	0.70	x 11	41.3	191.4	0.071	0.130	0.213	0.453
x 3/8	0.61	x 9.5	36.0	219.6	0.075	0.130	0.213	0.504
x 5/16	0.51	x 7.9	30.1	262.7	0.100	0.197	0.310	NR
x 1/4	0.41	x 6.4	24.2	326.8	0.117	0.230	NR	NR
L4 x 3.5 x 1/2	0.79	109 x 89 x 13	46.6	169.6	0.061	0.121	0.191	0.395
x 3/8	0.60	x 9.5	35.4	223.3	0.075	0.130	0.213	0.504
x 5/16	0.51	x 7.9	30.1	262.7	0.100	0.197	0.310	NR
x 1/4	0.41	x 6.4	24.2	326.8	0.117	0.230	NR	NR
L4 x 3 x 5/8	0.97	102 x 76 x 16	57.2	138.1	0.050	0.099	0.157	0.324
x 1/2	0.79	x 13	46.6	169.6	0.061	0.121	0.191	0.395
x 3/8	0.60	x 9.8	35.4	223.3	0.075	0.130	0.213	0.504
x 5/16	0.50	x 7.9	29.5	268.0	0.100	0.197	0.310	NR
x 1/4	0.41	x 6.4	24.2	326.8	0.117	0.230	NR	NR
L3.5 x 3.5 x 1/2	0.80	89 x 89 x 13	47.2	167.5	0.061	0.121	0.191	0.395
x 7/16	0.71	x 11	41.9	188.7	0.071	0.130	0.213	0.453
x 3/8	0.61	x 9.5	36.0	219.6	0.075	0.130	0.213	0.504
x 5/16	0.51	x 7.9	30.1	262.7	0.100	0.197	0.310	NR
x 1/4	0.42	x 6.4	24.8	319.0	0.117	0.230	NR	NR
L3.5 x 3 x 1/2	0.80	89 x 76 x 13	47.2	167.5	0.061	0.121	0.191	0.395
x 7/16	0.71	x 11	41.9	188.7	0.071	0.130	0.213	0.453
x 3/8	0.61	x 9.5	36.0	219.6	0.075	0.130	0.213	0.504
x 5/16	0.52	x 7.9	30.7	257.7	0.092	0.182	0.286	NR
x 1/4	0.42	x 6.4	24.8	319.0	0.117	0.230	NR	NR

Note: All thicknesses are expressed in inches. To convert to Mills, multiply by 1000. To convert to mm, multiply by 25.4

Miscellaneous Shapes

Single Angles

CAFECO® SprayFilm® WB 3 and WB 4 & ISOLATEK® Type WB 3 and WB 4

ASTM Desig.	W/D	Metric Desig.	M/D	Hp/A	1-Hour	1-1/2 Hour	2-Hour	3-Hour
L3.5 x 2.5 x 1/2	0.80	89 x 64 x 13	47.2	167.5	0.061	0.121	0.191	0.395
x 3/8	0.61		36.0	219.6	0.075	0.130	0.213	0.504
x 5/16	0.51	x 7.9	30.1	262.7	0.100	0.197	0.310	NR
x 1/4	0.41	x 6.4	24.2	326.8	0.117	0.230	NR	NR
L3 x 3 x 1/2	0.79	76 x 76 x 13	46.6	169.6	0.061	0.121	0.191	0.395
x 7/16	0.70	x 11	41.3	191.4	0.071	0.130	0.213	0.453
x 3/8	0.60	x 9.5	35.4	223.3	0.075	0.130	0.213	0.504
x 5/16	0.51	x 7.9	30.1	262.7	0.100	0.197	0.310	NR
x 1/4	0.41	x 6.4	24.2	326.8	0.117	0.230	NR	NR
L3 x 2.5 x 1/2	0.79	76 x 64 x 13	46.6	169.6	0.061	0.121	0.191	0.395
x 7/16	0.70	x 11	41.3	191.4	0.071	0.130	0.213	0.453
x 3/8	0.60	x 9.5	35.4	223.3	0.075	0.130	0.213	0.504
x 5/16	0.51	x 7.9	30.1	262.7	0.100	0.197	0.310	NR
x 1/4	0.41	x 6.4	24.2	326.8	0.117	0.230	NR	NR
L3 x 2 x 1/2	0.78	76 x 51 x 13	46.0	171.8	0.061	0.121	0.191	0.395
x 3/8	0.60	x 9.5	35.4	223.3	0.075	0.130	0.213	0.504
x 5/16	0.51	x 7.9	30.1	262.7	0.100	0.197	0.310	NR
x 1/4	0.41	x 6.4	24.2	326.8	0.117	0.230	NR	NR
L2.5 x 2.5 x 1/2	0.77	64 x 64 x 13	45.4	174.0	0.065	0.128	0.201	0.416
x 3/8	0.59	x 9.5	34.8	227.1	0.075	0.130	0.213	0.504
x 5/16	0.50	x 7.9	29.5	268.0	0.100	0.197	0.310	NR
x 1/4	0.40	x 6.4	23.6	335.0	0.133	0.263	NR	NR
L2.5 x 2 x 3/8	0.59	64 x 51 x 9.5	34.8	227.1	0.075	0.130	0.213	0.504
x 5/16	0.50	x 7.9	29.5	268.0	0.100	0.197	0.310	NR
x 1/4	0.41	x 6.4	24.2	326.8	0.117	0.230	NR	NR
L2 x 2 x 3/8	0.58	51 x 51 x 9.5	34.2	231.0	0.083	0.163	0.257	0.504
x 5/16	0.49	x 7.9	28.9	273.4	0.100	0.197	0.310	NR
x 1/4	0.40	x 6.4	23.6	335.0	0.133	0.263	NR	NR

Note: All thicknesses are expressed in inches. To convert to Mills, multiply by 1000. To convert to mm, multiply by 25.4